

Product Features

- Certified to EN 1433 Load Class F - 200,000 lbs - 4,182 psi
- Uses 'PowerLok' boltless locking system
- Suitable for use with S100K and H100K channels
- Manufactured from ductile iron to ASTM A 536-84 - Grade 304 65-45-12
- Anti-Shunt lugs



Specifications

General

The surface drainage system shall be ACO PowerDrain or SlabDrain, complete with ACO ductile iron slotted grate with 'PowerLok' locking as manufactured by ACO Polymer Products, Inc. or similar approved.

Materials

The covers shall be manufactured from ductile iron and have **minimum** properties as follows:

- **Independently certified to meet Load Class F to EN 1433 - 200,000 lbs - 4,182 psi**
- **Ductile iron to ASTM 536-84 - Grade 65-45-12**
- **Intake area of 166 sq. com per ½ meter of grate**

The overall width of 5.43" (138mm) and overall length of 19.68" (500mm). Slots measure at a maximum of 2.03" (52mm).

Grate

Grate is slotted ductile iron. Ductile iron ASTM 536-84 - Grade 65-45-12. After removal of grates there shall be uninterrupted access to the trench to aid maintenance. Grates can be used for PowerDrain or SlabDrain.

Installation

The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.


* delete as appropriate

ACO DRAIN

4" width - ductile iron slotted grate



Plan view




Side elevation



| Description | Part No. | Length inches (mm) | Width inches (mm) | Weight lbs. |
|--|--------------|-----------------------|----------------------|----------------|
| PowerLok grate SK1 ductile iron slotted steel grate - CI F | 96082 | 19.68 (500) | 5.43 (138) | 12.3 |

PowerLok locking mechanism



PowerLok Grate

Lug

PowerLok Device 'unlocked' position

PowerLok Rail

PowerLok Device 'locked' position

Recess in Grate

PowerLok Rail

ACO **PowerLok** is a patented boltless locking system. Grates are removed and replaced with minimum time and effort for ease of maintenance.

Lugs on the rail opposite the **PowerLok** device slots into recesses in the grate. The **PowerLok** device is used to engage the lug on the rail at two locations per grate to 'lock' the grate to the channel.

ACO Polymer Products, Inc.

Northeast Sales Office

9470 Pinecone Drive
Mentor, Ohio 44060
Tel: (440) 639-7230
Toll free: (800) 543-4764
Fax: (440) 639-7235

West Sales Office

825 W. Beechcraft St.
Casa Grande, AZ 85122
Tel: (520) 421-9988
Toll Free: (888) 490-9552
Fax: (520) 421-9899

Southeast Sales Office

4211 Pleasant Road
Fort Mill, SC 29708
Toll free: (800) 543-4764
Fax: (803) 802-1063

Follow us on



Electronic Contact:

info@ACODrain.us
www.ACODrain.us



© February 11, 2016 ACO Polymer Products, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO Polymer Products Inc. reserves the right to change the product and specifications without notice.