


Type 438D/437D Galvanized Steel Longitudinal Grate (ADA) Spec Sheet



Type 437D Galvanized Steel Longitudinal Grate

part no. 132550




Product Name	Part No.	Length in (mm)	Width in (mm)	Weight lbs
Type 438D Galvanized Steel Longitudinal Grate (ADA)	<b>132555</b>	39.37 (1000)	4.84 (123)	10.0
Type 437D Galvanized Steel Longitudinal Grate (ADA)	<b>132550</b>	19.69 (500)	4.84 (123)	4.2

# Type 438D/437D Galvanized Steel Longitudinal Grate (ADA) Spec Sheet



## DrainLok Locking Mechanism

ACO DrainLok is a patented, boltless locking system that removes the need for bolts and bars while improving the hydraulic capacity of the channel. DrainLok Clips lock into the channel's edge rail for rapid installation. ACO DrainLok grates are fitted with an anti-shunt mechanism that restricts unwanted grate movement when installed, improving durability and longevity of the system.



## Specification Summary

### General

The surface drainage system shall be ACO Drain K100, KS100, or H100K-8 channels, complete with ACO Type 438D/437D Longitudinal Galvanized Steel grate with DrainLok locking as manufactured by ACO, Inc. or similar approved.

### Installation

The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

### Materials

The covers shall be manufactured from galvanized steel and have minimum properties as follows:

- 16 gauge galvanized steel
- Intake area of 33.0 in<sup>2</sup> (212.90 cm<sup>2</sup>) per half meter of grate

Type 438D has a width of 4.84" (123 mm) and length of 39.37" (1000 mm).  
Type 437D has a width of 4.84" (123 mm) and length of 19.69" (500 mm).  
Slots measure 1.15" (29 mm) by 0.3" (8 mm).



ADA-compliant per The Americans with Disabilities Act of 2010, Section 302.3



ASME: A112.6.3 : Section 7.12  
Heel-resistant Strainers & Grates  
grate hole size ≤ 0.31" (8 mm)



Australian Standard AS 3996 - 2006 Clause 3.3.6:  
max slot length dependent on slot width for grates  
that are deemed Bicycle Tire Penetration Resistant.




EN1433 Load Class B  
28,101 lbs – 580 psi

## ACO, Inc.

© January 2026 ACO, Inc.

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions of use are suitable. ACO, Inc. reserves the right to change products and specifications without notice.



info@acousa.com  
www.acousa.com

