


Type 683 Galvanized Steel Heel-Resistant Brickslot 200 Access Unit



Product Name	Part No.	Invert in (mm)	Weight lbs
Type 683 Galvanized Steel Heel-Resistant Brickslot 200 Access Unit	138072	4.45 (113)	29.0

Note: Access unit may be used with catch basin and can also be used with channels

Type 683 Galvanized Steel Heel-Resistant Brickslot 200 Access Unit



Specification Summary

General

The surface drainage system shall be ACO Drain Brickslot, as manufactured by ACO, Inc. or approved equal.

Installation

The trench drain system shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Materials

The Brickslot top is manufactured from 11 gauge galvanized steel.

The nominal clear opening for Brickslot is $\frac{7}{8}$ " (22 mm) with two $\frac{5}{16}$ " (8 mm) slot openings and with a $\frac{1}{4}$ " (6 mm) bar between the two openings. Overall width is 9.37" (238 mm). For use with K200, KS200, SlabDrain (H200K-13, H200KS-13), and the K200 Series 900 catch basin. See separate ACO Spec Info Sheet for channel details. Brickslot rests in the grate seating of the channel, the anti-shunt lugs help prevent lateral movement and the weight of covering material keeps the unit secured. Access units have frames that fit catch basins with a separate unit that can be removed for maintenance.



ADA-compliant per The Americans with Disabilities Act of 2010, Section 302.3



Australian Standard AS 3996 - 2006 Clause 3.3.6: max slot length dependent on slot width for grates that are deemed Bicycle Tire Penetration Resistant.



ASME: A112.6.3 : Section 7.12 Heel-resistant Strainers & Grates grate hole size ≤ 0.31 " (8 mm)




EN 1433 Load Class C
56,202 lbs - 1,160 psi

ACO, Inc.

© January 2026 ACO, Inc.

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions of use are suitable. ACO, Inc. reserves the right to change products and specifications without notice.



info@acousa.com
www.acousa.com

