


# K1-901 In-Line Catch Basin w/ Plastic Base



## K1-901 (K100)


part no. 94608



Catch Basin Outlet	Size (SCH 40)	Invert in.	GPM	CFS
a	6.00"	19.99	505	1.12
b	4.00"	19.36	227	0.51
c	6.00"	27.30	604	1.35
d	4.00"	26.43	269	0.60
e	8.00"	27.30	1051	2.34
f	6.00"	26.43	593	1.32
g	4.00"	18.56	222	0.49
h	6.00"	25.85	586	1.32
i	4.00"	25.30	263	0.59

## K1-901 (KS100)

part no. 94609



Catch Basin Outlet	Size (SCH 40)	Invert in.	GPM	CFS
j	4.00"	20.68	235	0.52
k	4.00"	27.17	273	0.61
l	4.00"	18.99	224	0.50
m	6.00"	27.17	602	1.34
n	4.00"	19.30	226	0.50
o	4.00"	25.67	265	0.59

Note: These are pipe flow rates at specified outlets, NOT channel flow rates. Catch basin flow rates are listed without a trash bucket—using a trash bucket reduces flow.


## Trash Bucket

included with K1-901


Top



Side




Front



## Foul Air Trap (optional)

part no. 90854



# K1-901 In-Line Catch Basin w/ Plastic Base



Product Name	Part No.	Volume* gal	Weight lbs
K1-901 In-Line Catch Basin w/ Plastic Base (K100)	<b>94608</b>	12.3	52.6
K1-901 In-Line Catch Basin w/ Plastic Base (KS100)	<b>94609</b>	12.3	52.6
Foul Air Trap	<b>90854</b>	-	1.2

\*Volume is up to grate seat and without trash bucket.

## Specification Summary

### General

The catch basin shall be ACO Drain K1-901 Catch Basin, comprising of a top section, trash bucket and base as manufactured by ACO, Inc. or similar approved.

### Grates

Grates shall be specified. See separate ACO Spec Info grate sheets for details. After removal of grates and QuickLok® bar there shall be uninterrupted access to the catch basin to aid maintenance. Accepts all 0.5 m ACO K100 DrainLok grates or K100 QuickLok grates with optional QuickLok bar.

### Installation

The trench drain/catch basin system shall be installed in accordance with the manufacturer's installation instructions and recommendations.

### Materials

The catch basin top section shall be manufactured from polymer concrete with the minimum properties as follows:

- Compressive strength: 13,053 psi
- Flexural strength: 3,191 psi
- Water absorption: 0.07%
- Resistant to dilute acid and alkali
- Frost-proof
- Salt-proof

The nominal clear opening shall be 3.98" (100 mm) wide by 19.69" (500 mm) long. Overall width of 10.06" (255 mm) by 19.69" (500 mm) long. Type K1-901 catch basin assembly has overall depth of 29.03" (737 mm). Polymer concrete top units shall incorporate a cast in a galvanized or stainless steel frame manufactured with drillouts for channel connection and have a wall thickness of at least 0.59" (15 mm). Top units shall have horizontal cast in anchoring key features on the outside to ensure maximum mechanical bond to the surrounding bedding material and pavement surface. The base unit shall be an LLDPE plastic molding and incorporate molded plastic pipe stubs to facilitate pipe connection. The trash bucket shall be a polypropylene plastic molding.




EN1433 Load Class E  
134,885 lbs – 2,785 psi

## ACO, Inc.

© January 2026 ACO, Inc.

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions of use are suitable. ACO, Inc. reserves the right to change products and specifications without notice.



info@acousa.com  
www.acousa.com

