



Type 492D/497D/498D Slotted Plastic Grate Spec Sheet



Type 492D Slotted Plastic Grate

part no. 132720




Product Name	Part No.	Length in (mm)	Width in (mm)	Weight lbs
Type 492D black slotted plastic grate	132720	19.69 (500)	4.84 (123)	2.2
Type 497D gray slotted plastic grate	132266	19.69 (500)	4.84 (123)	2.2
Type 498D tan slotted plastic grate	132712	19.69 (500)	4.84 (123)	2.2

Type 492D/497D/498D Slotted Plastic Grate Spec Sheet



DrainLok Locking Mechanism

ACO DrainLok is a patented, boltless locking system that removes the need for bolts and bars while improving the hydraulic capacity of the channel. DrainLok Clips lock into the channel's edge rail for rapid installation. ACO DrainLok grates are fitted with an anti-shunt mechanism that restricts unwanted grate movement when installed, improving durability and longevity of the system.



Specification Summary

General

The surface drainage system shall be ACO Drain K100, KS100, or H100K-8 channels, complete with ACO Type 492D/497D/498D Slotted resin composite grate with DrainLok locking as manufactured by ACO, Inc. or similar approved.

Installation

The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Materials

The covers shall be manufactured from resin composite and have minimum properties as follows:

- UV stable resin composite
- Intake area of 22.2 in² (143.15 cm²) per half meter of grate

The overall width of 4.84" (123mm) and overall length of 19.69" (500mm). Slots measure 1.69" (42.92mm) by 0.3" (7.62mm).



ASME: A112.6.3 : Section 7.12
Heel-resistant Strainers & Grates
grate hole size ≤ 0.31" (8 mm)



Australian Standard AS 3996 - 2006 Clause 3.3.6:
max slot length dependent on slot width for grates
that are deemed Bicycle Tire Penetration Resistant.




EN 1433 Load Class C
56,202 lbs – 1,160 psi

ACO, Inc.

© January 2026 ACO, Inc.

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions of use are suitable. ACO, Inc. reserves the right to change products and specifications without notice.



info@acousa.com
www.acousa.com

