


H100KS-6 Stainless Steel Edge Rail Channel System




H100KS-6 Neutral Channel

Part No. 141804



H100KS-6 Closing End Cap

Part No. 296097



Outlet Flow Rates	Outlet Size	Invert Depth in (mm)	GPM	CFS
H100KS-6 Neutral Channel - 39.37" (1000 mm)	4.00" round	1.78 (45)	71.8	0.16

These are the pipe flow rates at the specified outlet, NOT channel flow rates

Product Name	Part No.	Invert Depth in (mm)	Weight lbs
H100KS-6 Neutral Channel - 39.37" (1000 mm)	141804	1.78 (45)	7.6
H100KS-6 Closing Cap	296097	1.78 (45)	0.1

Notes:

1. Add nominal 0.6" (15 mm) to invert depth for overall channel depth
2. Preformed 4" SCH 40 knock-out cast on underside of each channel
3. Use grate removal tool to remove grates (Part No. 01318)

H100KS-6 Stainless Steel Edge Rail Channel System



Specification Summary

General

The surface drainage system shall be ACO Drain SlabDrain H100KS-6 complete with gratings secured with DrainLok® as manufactured by ACO, Inc. or equal approved.

Grates

Grates should be specified. See separate ACO Spec Info grate sheets for details. After removal of grates, there shall be uninterrupted access to the trench to aid maintenance.

Installation


The trench drain system shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Materials

The trench system bodies shall be manufactured from polyester polymer concrete with minimum properties as follows:

- Compressive strength: 13,000 psi
- Flexural strength: 3,100 psi
- Water absorption 0.07%
- Frost proof
- Salt proof
- Dilute acid and alkali-resistant


The nominal clear opening shall be 4.00" (100 mm) with overall width of 5.12" (130 mm). Pre-cast units shall be manufactured with neutral invert and have a wall thickness of at least 0.50" (13 mm). Each unit will feature a male to female interconnecting end profile. The stainless steel edge rail will be integrally cast in by the manufacturer to ensure maximum homogeneity between polymer concrete body and edge rail. Each edge rail shall be at least 1/8" (3 mm) thick.

 EN1433 Load Class D
89,924 lbs – 1,856 psi

ACO, Inc.

© January 2026 ACO, Inc.

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions of use are suitable. ACO, Inc. reserves the right to change products and specifications without notice.



info@acousa.com
www.acousa.com

