

ADA-compliant Surface Slot Pattern

Abrasion-resistant Surface

Monolithic Build

Interconnecting End Profiles

Directional Arrows for Install

High Strength Polymer Concrete


Exceeds AASHTO HS-25 Requirements

Profiled Side Walls

4" Internal Width Trench

Compatible with ACO Installation Devices

Catch Basin Outlet Connections



MonoBloc ADA 100

Sloped Monolithic Trench Drain
4" Internal Width

Durable ADA-Compliant Drainage

MonoBloc ADA 100 trench drain is ideal for demanding industrial and transportation applications with high heavy-duty vehicle loading and traffic and expected regular pedestrian traffic.

The monolithic construction provides many benefits over fully grated systems, especially in applications where the drainage cannot be positioned outside the flow of traffic.




EN 1433 Load Class E
134,885 lbs – 2,785 psi



ADA-compliant per The Americans with Disabilities Act of 2010, Section 302.3



ASTM E303-22 Pendulum
Slip Resistance Test



Typical Applications


- Truck Stops
- Gas Stations
- Parking Lots
- Parking Garages
- Shopping Districts
- Commercial Areas
- Light Industrial Areas
- Internal Applications

Monolithic Ingenuity

ADA 100's single-piece construction provides unique benefits over removable-grate systems, especially in applications where the drainage cannot be positioned outside the flow of traffic:

- Solid build
- High structural strength
- Excellent load and hydraulic capacities
- No loosening from vibrations
- No grates outside of access/outlet channels
- Lockable PowerLok grate for access channel
- Quick installation reduces road closures
- More economical than grated systems

Channel Options



Neutral, Access and Outlet Channels

NEUTRAL CHANNEL

- 1 m length
- 5 depths

SLOPED CHANNEL

- 1 m length
- 40 m system




ACCESS CHANNEL

- provides access for maintenance via grated opening
- 1 m length
- 5 depths
- 19.69" (0.5 m) ductile iron grate

CATCH BASIN ACCESS CHANNEL


- high-capacity evacuation of system via catch basin connection
- 1 m length
- 5 depths
- 19.69" (0.5 m) ductile iron grate
- 928–2,867 GPM

ADA 100 Channel



ADA 100 Channels	Invert Depth, in (mm)	Weight, lbs
Neutral	5.91 (150)	81.4
	7.87 (200)	90.2
	9.84 (250)	98.9
	11.81 (300)	107.5
	13.78 (350)	115.8
Sloped*	6.10 (155) – 13.94 (354)	77.7 – 112.6
Access	5.91 (150)	76.9
	7.87 (200)	85.0
	9.84 (250)	107.5
	11.81 (300)	116.1
	13.78 (350)	124.5
Catch Basin Access	5.91 (150)	82.0
	7.87 (200)	90.7
	9.84 (250)	99.5
	11.81 (300)	107.9
	13.78 (350)	116.5

*Sloped channels fit between neutral channels to give continuous 0.5% slope across 125' (40 m).



ACO, Inc.

West Sales Office
825 W. Beechcraft St.
Casa Grande, AZ 85122
Tel: (520) 421-9988
info@acousa.com
www.acousa.com

Northeast Sales Office
9470 Pinecone Drive
Mentor, OH 44060
Tel: (440) 639-7230

Southeast Sales Office
481 Munn Rd. Ste 225
Fort Mill, SC 29715
Tel: (440) 639-7230

© August 2026 ACO, Inc.
All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions of use are suitable. ACO, Inc. reserves the right to change products and specifications without notice.

ACO. we care for water

